

SECTION 1:
MANUFACTURER

MATERIAL SAFETY DATA SHEET
SPECIALTY INK CO., INC.
20 DUNTON AVE.
DEER PARK, N.Y. 11727
PHONE NUMBER 631-586-3666
EMERGENCY PHONE 1-800-688-4005
FAX NUMBER 631-586-3874

PAGE 1

DATE PREPARED
02/06/01

INK NAME: MEAT & CHEESE

HEALTH: 0 CODE: 0=MINIMAL
FLAMMABILITY: 3 1=SLIGHT
REACTIVITY: 0 2=MODERATE
PERSONAL PROTECTION: A 3=SERIOUS
4=SEVERE

SECTION 2: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	ACGIH-TLV	OSHA-PEL	CAS NO
SPEC DENATURED ALC 23A	37.00	1000 PPM	1000 PPM	64-17-5

SECTION 3: PHYSICAL & CHEMICAL CHARACTERISTICS

BOILING POINT: 173 F
MELTING POINT: -121 F
VAPOR DENSITY: 1.5
SPECIFIC GRAVITY: .8151
REACTIVITY IN WATER: NONE
SOLUBILITY IN WATER: COMPLETELY SOLUBLE
AUTO IGNITION: 545 F
VAPOR PRESSURE: 43 MM HG
APPEARANCE & ODOR: MOBILE LIQUID
APPEARANCE & ODOR: NO ODOR
LEL/UEL %: 4.3 19
FLASH POINT: 63 F
METHOD: CLOSED CUP

SECTION 4: FIRE & EXPLOSION DATA

EXTINGUISHING MEDIA: WATERSPRAY
SPECIAL FIRE PROCEDURES: INK IS MOSTLY WATER AND AFTER THE
SPECIAL FIRE PROCEDURES: DENATURED ALCOHOL BURNS OFF, THE
SPECIAL FIRE PROCEDURES: FIRE WILL GO OUT.
UNUSUAL HAZARDS: NONE

SECTION 5: REACTIVITY DATA

STABLE, Y=YES, N=NO : Y
CONDITIONS TO AVOID: OPEN FLAME
INCOMPATIBILITY: NONE
HAZARDOUS DECOMPOSITION: NONE
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: NONE

SECTION 6: HEALTH HAZARDS

ACUTE: NONE

Kids Washable

MSDS: Child Safe Stamp Ink

MATERIAL SAFETY DATA SHEET

Pro ColorFlex Ink Corporation
30672 San Antonio Street
Hayward, CA 94545
Tel: 510-477-0845 Fax: 510-477-0336

Emergency Telephone No.
510-477-0845
Date Prepared: 07/02/97
Prepared By: R. Duarte
Revised: 06/11/98

PRODUCT HMIS RATING
Health.....1 (Slight)
Flammability.....0 (Minimal)
Reactivity.....0 (Minimal)

SECTION A - PRODUCT INFORMATION

Trade Name: Child Safe Stamp Ink
Product Class: Stamp Ink
Manufacturer: Pro ColorFlex Ink Corp.
30672 San Antonio Street
Hayward, CA 94545

Product ID No. **Varies with color**

SECTION B - HAZARDOUS COMPONENTS

Component	CAS No.	Hazard	App. Wt. %	TLV	OSHA PEL
Propylene Glycol	57-55-6	Slight Irritant	40-45	Not established	Not established

Non Hazardous and other ingredients below reportable levels.

SECTION C - PHYSICAL DATA

APPEARANCE: Colored Liquid
PHYSICAL STATE: Thin Liquid
EVAPORATION RATE (vs BUTYL ACETATE): Slower
% VOLATILE BY WEIGHT: N/A

BOILING RANGE: 450 - 475 °F
ODOR: Mild Glycol
VAPOR DENSITY (vs Air): Heavier
SOLUBILITY IN WATER: Complete

SECTION D - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 350 °F
FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: Water fog, CO₂, foam or dry chemical.
SPECIAL FIREFIGHTING PROCEDURES: Normal firefighting procedures may be used.
UNUSUAL FIRE AND EXPLOSION HAZARDS: No special requirements. Container may burn and leak in heat of fire

SECTION E - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: None established.
PRIMARY ROUTES OF ENTRY: Skin contact.
EFFECTS OF ACUTE OVEREXPOSURE: May cause minimal eye irritation.

SECTION F - EMERGENCY FIRST AID PROCEDURES

EYES: In case of contact, immediately flush eyes with plenty of clean running water for at least 15 minutes, lifting the upper and lower lids occasionally.